

# SOFTLINE COMPACT

Softline Series

## MOUNTING BRACKETS

All dimensions in mm. Inches in brackets.



| Dimensions | mm  | inches | mm  | inches | mm  | inches | mm  | inches |
|------------|-----|--------|-----|--------|-----|--------|-----|--------|
| Height     | 300 | 11.81  | 450 | 17.72  | 600 | 23.62  | 700 | 27.56  |
| A          | 65  | 2.56   | 65  | 2.56   | 65  | 2.56   | 65  | 2.56   |
| B          | 119 | 4.69   | 99  | 3.90   | 99  | 3.90   | 99  | 3.90   |
| C          | -   | -      | 269 | 10.59  | 419 | 16.50  | 519 | 20.43  |
| D          | 153 | 6.02   | 303 | 11.93  | 453 | 17.83  | 553 | 21.77  |
| E          | 185 | 7.28   | 335 | 13.19  | 485 | 19.09  | 585 | 23.03  |



# SOFTLINE COMPACT

## Softline Series

**K1, P+ & K2 LUG POSITIONS** (New as of June 2016).  
All dimensions in mm. Inches in brackets.



| L           | K1  |      |            |    | P+/K2 |      |     |    |
|-------------|-----|------|------------|----|-------|------|-----|----|
|             | A   |      | B          |    | C     |      | D   |    |
|             | mm  | in   | mm         | in | mm    | in   | mm  | in |
| 400         | 117 | 4.60 | -          | -  | 133   | 5.24 | -   | -  |
| 500 - 1100  | 150 | 5.90 | -          | -  | 133   | 5.24 | -   | -  |
| 1200 - 1600 | 150 | 5.90 | -          | -  | 133   | 5.24 | -   | -  |
| 1800 - 2000 | 150 | 5.90 | (L/2) + 17 |    | 133   | 5.24 | L/2 |    |

### CONNECTIONS

Each radiator comes with 1/2" inlet connections as standard.

### PIPING OPTIONS



# SOFTLINE COMPACT

Softline Series

## EN 442 CERTIFICATION DATA - CETIAT TESTED IN ACCORDANCE WITH BS EN 442

| Type                                    | K1   |       |       |       | P+    |       | K2    |       |       |       |
|---|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|   | 300  | 450   | 600   | 700   | 450   | 600   | 300   | 450   | 600   | 700   |
| Height                                  | 300  | 450   | 600   | 700   | 450   | 600   | 300   | 450   | 600   | 700   |
| W/m at 75/65/20                         | 509  | 756   | 980   | 1117  | 1055  | 1345  | 982   | 1371  | 1732  | 1961  |
| n-coefficients                          | 1.32 | 1.31  | 1.29  | 1.29  | 1.34  | 1.33  | 1.33  | 1.33  | 1.33  | 1.34  |
| Heated surface area (m <sup>2</sup> /m) | 2.09 | 3.37  | 4.66  | 5.51  | 3.84  | 5.24  | 3.51  | 5.62  | 7.74  | 9.15  |
| Weight (kg/m)                           | 9.31 | 14.51 | 19.70 | 22.90 | 22.04 | 29.80 | 16.80 | 25.90 | 35.00 | 40.53 |
| Water contents (l/m)                    | 1.89 | 2.57  | 3.25  | 3.77  | 5.15  | 6.60  | 3.70  | 5.15  | 6.60  | 7.63  |
| Wall to tap centre (mm)                 | 51   | 51    | 51    | 51    | 62    | 62    | 73    | 73    | 73    | 73    |

## PRESSURE DROPS

