

**TRAVIS PERKINS GROUP**  
**DECLARATION OF PERFORMANCE**  
No:TDS00108-DOP

**1. Product Type:** TILE ADH W/PROOF

**2 Unique Identification Code(s):** 879414, 879415

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Normal dispersion adhesive with extended open time and reduced slip for internal tiling

**4. Manufacturer:** Manufactured by a member of the Travis Perkins Group  
Lodge Way House  
Harlestone Road  
Northampton  
NN5 7UG

**5. Authorised Representative:** Not Applicable

**6. System of System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:** System 3

**7. Harmonised Standard:** EN12004:2007+A1:2012

**8. Notified Body:** The notified body No.NB1289 carried out the determination of the product type on the basis of type testing on samples taken by the manufacturer under system 3 and issued the test report (131338)-5696

**9. Declared Performance** D1E

Essential Characteristics	Performance	Harmonised technical specification
Reaction to Fire	F	EN12004:2007+A1:2012
Initial Shear adhesion strength	$\geq 1 \text{ N/mm}^2$	
Shear adhesion strength after heat aging	$\geq 1 \text{ N/mm}^2$	
Extended open time: tensile adhesion strength	$\geq 0.5 \text{ N/mm}^2$ after not less than 30 minutes	
Release of dangerous substances	See MSDS	

- 10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**Name and function:**

**Place and date of issue:**

**Signature:**