

## TECHNICAL DATA

# Geocel® Silicone Sealant Remover



Geocel® Silicone Sealant Remover is an acidic thixotropic gel for breaking down the difficult to remove residues and smears of cured silicone. It is therefore, ideal for the refurbishment of sanitaryware, door or window frames, worktops etc. It is also suitable for removing cured silicone where product has been mistakenly applied.

### Main Uses

Removing unwanted cured silicone sealant.

### Benefits:

- Ideal for refurbishment work or removing areas of misapplied silicone sealant
- Easy to use
- Suitable for use on the following surfaces: coated metals, ceramic tiles, plastics, laminated board, painted surfaces, glass and aluminum
- Available in 100ml 'e' tubes with easy to read instructions

### INSTRUCTIONS FOR USE

1. Unwanted silicone sealant should be cut back as close to the surface as possible using a sharp blade.
2. Take care not to apply Geocel® Silicone Sealant Remover to areas of correctly applied silicone sealant. These areas may be protected using masking tape.
3. Squeeze a liberal coat of Geocel® Silicone Sealant Remover to the affected area.
4. Allow to stand for 2 hours. Wipe clean with a paper tissue or dry cloth and ensure all traces of solvent are removed.
5. If traces of silicone sealant still remain, repeat application.
6. Surfaces should be degreased with a solvent such as methylated spirit before applying fresh sealant.

### LIMITATIONS

#### DO NOT USE ON NYLON.

The gel should be applied to dry surfaces and under dry weather conditions. If the gel comes into contact with water, the active ingredients will be deactivated and the gel rendered un-usable. The gel will not completely dissolve silicone sealant but will break down the adhesion of the sealant to the substrate to facilitate removal.

### STORAGE

Store in dry conditions between 5°C and 25°C. Both the tube and the bottle should be kept tightly sealed when not in use.

### HEALTH AND SAFETY

A full health and safety data sheet is available giving information for safe use.

**Important Note:** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damage.