

SL-X SINGLE TANK NON-ELECTRIC WATER SOFTENER

EAN	5027639900308
Product code	900308
People	Up to 6
Height	576mm
Depth	547mm
Depth (With Connectors)	572mm
Width	343mm
Approximate regeneration time	16 Minutes
Resin volume	15.5 Litre
Salt used per regeneration	590 gm
Water used per regeneration	25 Litre
Flow Rate @ 1 bar Pressure Drop	2100 Litres / Hour
Flow Rate @ 2 bar Pressure Drop	2700 Litres / Hour
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Installation Orientation	Rear Only
Minimum/Maximum Operating Temp	2° - 49°C
Minimum/Maximum Working Pressure	1.5 bar Max / 6 bar Minimum*
* Pressure Reducing Valve must be used over 6 bar	
What salt to use	Tablet or Block
Warranty	5 Years parts 2 Years Labour*

TECHNICAL HELPLINE 01785 811636



Requires one of the following installation kits	
900803	15mm Standard Installation Kit
900858	22mm Hi-Flow Hoses x 2
900827	Combi installation Kit
900810	22mm Hi-Flow Installation Kit

*** IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

Hardness Level	125	150	200	250	350	500	850
Litres Between Regeneration	2158	1779	1325	1060	757	530	303