

# Serenitie

Wall Mounted 3TH Bath Mixer





## Product features:

- Metal construction throughout
- Quarter turn handle action for precise flow control
- Custom designed for lower range pressures
- · Fixed spout to prevent accidental water damage
- Adjustable to suit various thickness of wall


Packaged properties:

Box length (mm): 395 Box depth(mm): 95
Box width(mm): 165 Boxed weight (Kg): 2.8

Includes pop up waste?: No Additional comments:

Includes mounting screws

#### **Product dimensions:**



Product mounted where: Wall

• Recommended hole size: 35, 42, 35 mm


Overall Height / projection: 157 mm
Exit reach: 151 mm
Exit height: 39 mm
Base size: 55, 65, 55 mm

• Inlet centre distance(s): 240 mm

• Min. fitting depth required: 48-61 mm

Max. surface depth:

## **Product flow characteristics:**



- Min / Max water pressure (bar): 0.20\* / 5.00
- Part G max. mixed flow rate at 3 bar (I/m): 41
- Inlet connection type / length: Fixed / mm
- Inlet (plumbing connection) / outlet size: 3/4" M /
- Product flow characteristics: Single flow Non return valve(s) supplied or position:
- Aerator type: Grey flow straightener
- Control valve type: 3/4" QT CD (8-24 extended)
- Includes output diverter?: No
- Inlet meshed particle filters included:
- Shower hose type / length:

### Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
   Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives