

# BM Zero

ANTI-FREEZE

Available  
in 5L & 23L  
containers

A glycol based closed-loop universal anti-freeze with corrosion, scale inhibitors and biocide. Suitable for use with solar, ground source heat pumps and central heating circuits. Dilute at point of use.

**Protects central heating system from water freezing during cold weather conditions. Helps prevent limescale build-up and corrosion.**

**By dosing the system with BMZero, it will provide the following benefits:**

- ✓ Prevents system water from freezing
- ✓ Protection against limescale, corrosion
- ✓ NSF performance standard approved
- ✓ Fully compliant with **BS 7593:2019**

“For systems that are not used over the winter months and which might be exposed to very low temperatures, protection from freezing should be taken into account. A suitable inhibited anti-freeze product that provides frost protection to the required level, and is suitable for the system components”.

**Note:** BMZero is available in 5L, 23L containers. The minimum dosage rate to achieve the NSF performance standard is 25L per 100L system capacity.

A 25% solution will protect to -11°. Preferentially, BMZero should be diluted with demineralised water, softened water or naturally hard/soft water.

Inhibited anti-freeze is a freezing point depressant suitable for use with conventional indirect central heating systems including under-floor installations, ground source heat

For details of your local stockist or for more information visit [www.boilermag.com](http://www.boilermag.com) or contact +44 (0)114 225 0624 or [service@boilermag.com](mailto:service@boilermag.com)