Geberit Mapress Copper bend with plain end (gas)

Example image



APPLICATION PURPOSES

- For natural gases
- For liquefied gases
- For natural and liquefied gases

CHARACTERISTICS

- Pressing indicator
- Leaky if unpressed
- Marked in yellow
- Seal ring made of HNBR, yellow
- Pressing socket with yellow protection plug

TECHNICAL DATA

Product material	Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, ø mm	arc °	L cm	H cm	Z cm
34521	12	15	45	2.8	3.8	0.8
34522	15	18	45	2.9	3.9	0.9
34523	20	22	45	3.2	4.4	1.1
34524	25	28	45	3.7	4.5	1.4
34525	32	35	45	4	4.9	1.4

Art. no.	DN	d, ø mm	arc °	L cm	H cm	Z cm
34526	40	42	45	4.7	5.7	1.7
34527	50	54	45	5.7	6.8	2.2
34507	12	15	90	3.8	5.1	1.8
34508	15	18	90	4.2	5.3	2.2
34509	20	22	90	4.7	6	2.6
34510	25	28	90	5.7	6.5	3.4
34511	32	35	90	6.5	7.4	3.9
34512	40	42	90	7.6	8.6	4.6
34513	50	54	90	9.5	10.6	6